



## USED PORTABLE POWER

Developing Technology for Tomorrow's Power Needs.

# Denyo

## Technical

<b>Model</b>	DCA25
<b>Type</b>	Skid
<b>Speed</b>	1500 RPM
<b>Phase/Voltage</b>	3 / 240-415
<b>Frequency</b>	50 Hz
<b>Standby Power kVA/ kW</b>	22kVA / 17.6kW
<b>Prime Output kVA/ kW</b>	20 kVA / 1.6 kW
<b>Noise Level (dBA @ 7m)</b>	62
<b>Frame</b>	Heavy Duty Canopy

## Engine

<b>Manufacturer</b>	Isuzu
<b>Engine Model</b>	C240, 4LE1
<b>Type</b>	Indirect
<b>Starting</b>	Electric start
<b>Fuel</b>	Diesel
<b>Run Time</b>	16 - 24 hrs
<b>Consumption</b>	2.8 – 3.0 L/h @75%
<b>Tank Capacity</b>	65 L
<b>Output Rating kWm</b>	18.4

## Alternator

<b>Alternator Brand</b>	Denyo
<b>Type</b>	Brushless
<b>Harmonic Distortion</b>	Less than 5%
<b>Protection Class</b>	IP 23
<b>Insulation Class</b>	Class H

## Canopy

<b>Lift</b>	Centre Lift
<b>Build</b>	Heavy Duty Mild Steel 2 Pac Paint Finish
<b>Base</b>	Heavy Duty Skid
<b>Control Panel</b>	Viewing Window Provided

## Controls

<b>Control Panel</b>	Key Start with Engine Protection
<b>Metering</b>	Amps/Ph, Volts/Ph, Hz, RPM
<b>Protection</b>	Three Pole Output Circuit Breaker

## Dimensions & Weight

<b>Length</b>	1.58 - 1.85 Cm
<b>Width</b>	0.65 – 0.75 Cm
<b>Height</b>	0.9 – 1.0 Cm
<b>Weight</b>	560 - 730 Kg

## Options

<b>Outlets</b>	Weather protected IP33 & Weatherproof IP66
<b>Protection</b>	Adjustable RCD
<b>Fuel</b>	Three Way Changeover Valves For External Tanks