



## PORTABLE POWER

# AIRMAN®

### Technical

Model	SDG25
Type	Skid
Speed	1500 RPM
Phase/Voltage	3 / 240-415
Frequency	50 Hz
Standby Power kVA/ kW	22kVA / 17.6kW
Prime Output kVA/ kW	20 kVA / 16 kW
Noise Level (dBA @ 7m)	61
Frame	Heavy Duty Canopy

### Engine

Manufacturer	Isuzu
Engine Model	4LE1
Type	Indirect
Starting	Electric start
Fuel	Diesel
Run Time	19 - 25 hrs
Consumption	2.8 L/h @75%
Tank Capacity	70 L
Output Rating kWm	19.1
Cubic Capacity	2.18

### Alternator

Alternator Brand	Taiyo
Type	Brushless
Harmonic Distortion	Less than 5%
Protection Class	IP 23
Insulation Class	Class H

### Controls

Control Panel	Key Start with Engine Protection
Metering	Amps/Ph, Volts/Ph, Hz, RPM
Protection	Three Pole Output Circuit Breaker

### Dimensions & Weight

Length	1.58 Cm
Width	0.70 Cm
Height	0.95 Cm
Weight	580 Kg

### Options

Outlets	Weather protected IP33 & Weatherproof IP66
Protection	Adjustable RCD
Fuel	Three Way Changeover Valves For External Tanks